

BRAZIL

AXON' CABLE INDUSTRIA E COMÉRCIO LTDA
Av. das Américas, 500 – Bl. 9 – Sala 208.
Rio de Janeiro, RJ, CEP 22.640-100
TEL.: +55 21 3596-8002
e-mail: salesbrazil@axon-cable.com

» CANADA

AXON' CABLE CANADIAN OFFICE
MONTREAL, QUEBEC
TEL.: +1 514 898 2044
e-mail: sales@axoncable.com

» CHINA

AXON' INTERCONNECT LTD
High Tech Industrial Park, Chang Bao Xi Road
Ronggui, 528306
SHUNDE, GUANGDONG
TEL.: +86 757 2838 7200 – FAX: +86 757 2838 7212
e-mail: sales@axon-interconnect.com

» GERMANY

AXON' KABEL GMBH
Postfach 1131 – 71201 LEONBERG
Hertichstr. 43 – 71229 LEONBERG
TEL.: +49 7152-97992-0
e-mail: sales@axon-cable.de

» HUNGARY

AXON' KÁBELGYÁRTÓ KFT.
Külső-Szegedi út 104.
H-6000 KECSKEMÉT
TEL.: +36 76 508 195
e-mail: axon@axon-cable.hu

» INDIA

AXON' INTERCONNECTORS & WIRES PVT LTD
Plot No.102, KIADB Hitech Defense and Aerospace Park
Unachur Village, B.Marenahalli, Jala Hobli, Budigere Post
Bangalore North Taluk,
Bangalore Urban-562 129
TEL.: +91 (0) 806 816 2966 – FAX: +91 (0) 806 816 2999
e-mail: sales@axon-cable.in

DHRUV: your Indian offset partner
DHRUV AXON' INTERCONNECT PRIVATE LTD

Plot No.102, SW Part-A,
KIADB Hitech Defense and Aerospace Park,
Unachur Village, B.Marenahalli,
Jala Hobli, Budigere Post,
Bangalore North Taluk,
Bangalore Urban-562



VISIT OUR WEBSITE
www.axon-cable.com



» JAPAN

AXON' CABLE JAPAN OFFICE
2F-B Marusa Bldg, 1-3-16 Minami Chitose
Nagano-shi, Nagano, 380-0823
TEL./FAX: +81 26 217 6728
e-mail: axon-japan@axon-cable.com

» LATVIA

AXON' CABLE SIA
Višķu Iela, 21 C
LV-5410 DAUGAVPILS
TEL.: +371 6540 78 91
e-mail: axon@axoncable.lv

» MEXICO

AXON' INTERCONEX, S.A. DE C.V.
Av. Peñuelas 21-A1.
Industrial San Pedrito Peñuelas
Querétaro Park
76148 Querétaro, Qro.
TEL.: +52 442 215 2713
e-mail: axon-mexico@axoncable.com

» SINGAPORE

AXON' CONNECT PTE LTD
3 Ang Mo Kio Street 62,
#04-02 Link@AMK,
Singapore 569139
TEL.: +65 6250 3169
e-mail: sales.singapore@axon-cable.com

» SPAIN

AXON' CABLE SPANISH OFFICE
C/Capitán Haya, N°1, Planta 15
28020 MADRID
TEL.: +34 91 418 43 46 – FAX: +34 91 556 28 80
e-mail: sales@axon-cable.com

» UNITED KINGDOM


AXON' CABLE LTD
AXON' AGORA – Admiralty Park
ROSYTH – DUNFERMLINE
FIFE KY11 2YW
TEL.: +44 1383 421500
e-mail: sales@axon-cable.co.uk

» USA

AXON' CABLE INC.
1316 N Plum Grove Road
SCHAUMBURG, IL. 60173
TEL.: +1 847 230 7800
e-mail: sales@axoncable.com

© 2021, AXON' CABLE – ALL RIGHTS RESERVED – RELEASED JANUARY 2021/A – PHOTOS AXON' – D-CLICK®: REGISTERED TRADEMARK OF AXON' CABLE – ALL INFORMATION CONTAINED IN THIS BROCHURE IS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.

Waterproof Micro-D IP68 connectors



Expert in Micro-D connectors

As a specialist in advanced interconnect solutions, Axon' Cable has extensive experience in micro-miniature solutions based on the highly reliable Twist Pin contact technology.

By its very design, the Micro-D connector system meets all the requirements of robustness, durability, low contact resistance, high current, dielectric strength, shock and vibration.

With 1.27 mm (.050") contact spacing, Micro-D connectors, half the pitch of D-Sub connectors, represent an excellent solution for saving both space and weight.

In addition to a complete range of QPL qualified Micro-D connectors to MIL-DTL-83513, Axon' also offers Micro-D PCB connectors and cable assemblies in both metal and plastic bodied versions.

In addition to circular and rectangular Micro-D connectors and assemblies, Axon' Cable offers Nano-D connectors and jumpers compliant to the MIL-DTL-32139 specification.

About Axon' Cable


Headquartered in the beautiful Champagne region of France, Axon' is a worldwide leader in specialist interconnect. The company excels in the design and manufacture of wires, cables, terminated harnesses and interconnect solutions for high technology applications.

What is IP68 ?

The IP Code (Ingress Protection Code) is an IEC standard 60529 that classifies and rates the degree of protection provided by mechanical casings and electrical enclosures against intrusion, dust, accidental contact, and water. IP68 provides protection in water at least 1m deep for 60 minutes and is also dustproof.

Micro-D IP68 for severe environments

- ▲ Designed and IP68 tested to withstand severe environments.
- ▲ Watertight after mating.
- ▲ Protected against water immersion from 1 to 3 meters for 60 minutes.
- ▲ Robust: excellent resistance to shock and vibration.
- ▲ Lightweight and space saving solution.
- ▲ Custom designed solution.




Waterproof Micro-D Connectors

From auto racing to shallow water military crossings, harsh environments require rugged and highly reliable interconnect solutions especially when they come into contact with dust or water. Axon' Cable has expanded its range of Micro-D connectors by developing a waterproof Micro-D rectangular connector. IP68 approved, this innovative solution meets all the performance requirements of MIL-DTL-83513, while delivering significant water and dust protection thanks to a three-lip fluorosilicone rubber seal. The solution is also compatible with Combo-D, optical Micro-D, custom-designed and high-density (Hermit-Nano) connectors. IP68 Micro-D connectors can be equipped with Axon's highly popular, fast-latching D-click® - an easy-to-use mating and locking system, with no tooling required.



Waterproof Micro-D dimensions



	A ± 0.25 (±.010)	B max. Male	C -0.46/+0.25 (-.018/+0.010)	D ± 0.13 (±.005)	E ± 0.25 (±.010)	F max. Male	G max.
9 P	19.69 .775	8.48 .334	9.91 .390	14.35 .565	7.57 .298	4.69 .185	6.86 .270
15 P	23.50 .925	12.29 .484	13.72 .540	18.16 .715	7.57 .298	4.69 .185	6.86 .270
21 P	27.31 1.075	16.10 .634	17.53 .690	21.97 .865	7.57 .298	4.69 .185	6.86 .270
25 P	29.85 1.175	18.64 .734	20.07 .790	24.51 .965	7.57 .298	4.69 .185	6.86 .270
31 P	33.66 1.325	22.45 .884	23.88 .940	28.32 1.115	7.57 .298	4.69 .185	6.86 .270
37 P	37.47 1.475	26.26 1.034	27.69 1.090	32.13 1.265	7.57 .298	4.69 .185	6.86 .270
51DR P	46.36 1.825	35.15 1.384	36.58 1.440	41.02 1.615	7.57 .298	4.69 .185	6.86 .270
51 P	36.20 1.425	24.99 .984	26.42 1.040	30.86 1.215	8.66 .341	5.79 .228	7.87 .310
69 P	43.82 1.725	32.61 1.1284	34.04 1.340	38.48 1.515	8.66 .341	5.79 .228	7.87 .310
100 P	54.86 2.160	35.15 1.384	36.37 1.432	45.72 1.800	9.75 .384	6.88 .271	9.14 .360

Applications

MIL-AERO | AUTO RACING | MILITARY LAND | ANY APPLICATION REQUIRING WATERTIGHT EQUIPMENT UP TO 3 METERS DEEP